



Specifications :

Voltage rating: 250V AC / DC
 Current rating: 3A AC / DC
 Withstanding voltage: 1000V AC/minute
 Temperature range: -40°C~+105°C
 Insulation resistance: $\geq 1000\text{M}\Omega$
 Contact resistance: $\leq 20\text{m}\Omega$
 After environmental testing: $\leq 30\text{m}\Omega$

Reference Informations:

*Material:

PIN: Brass/Tin Plated

Wafer: PBT,UL94V-0

Color: Black

Poles	Dimensions (mm)		Poles	Dimensions (mm)	
	A	B		A	B
2*2P	2.54	7.46	2*17P	40.64	45.56
2*3P	5.08	10.00	2*18P	43.18	48.10
2*4P	7.62	12.54	2*19P	45.72	50.64
2*5P	10.16	15.08	2*20P	48.26	53.18
2*6P	12.70	17.62	2*21P	50.80	55.72
2*7P	15.24	20.16	2*22P	53.34	58.26
2*8P	17.78	22.70	2*23P	55.88	60.80
2*9P	20.32	25.24	2*24P	58.42	63.34
2*10P	22.86	27.78	2*25P	60.96	65.88
2*11P	25.40	30.32	2*26P	63.50	68.42
2*12P	27.94	32.86	2*27P	66.04	70.96
2*13P	30.48	35.40	2*28P	68.58	73.50
2*14P	33.02	37.94	2*29P	71.12	76.04
2*15P	35.56	40.48	2*30P	73.66	78.58
2*16P	38.10	43.02	2*31P	76.20	81.12
			2*32P	78.74	83.66

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, \pm
 .X \pm 0.30
 .XX \pm 0.20
 .XXX \pm 0.10
 ANG \pm

PJECTION

照片框

ORDER INFORMATION

MOD-D-2Xxx-LF

SERIES

LEADFREE

2X02:04WAY

2X32:64WAY

DIP 180°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: WAFER 2.54mm DIP TYPE