



RECOMMENDED P.C.B LAYOUT

POSITION	A	B	C
10	12.54	5.08	9.64
14	15.08	7.62	12.18
16	16.35	8.89	13.45
20	18.89	11.43	15.99
24	21.43	13.97	18.53
26	22.70	15.24	19.80
30	25.24	17.78	22.34
34	27.78	20.32	24.88
40	31.59	24.13	28.69
44	34.13	26.67	31.23
50	37.94	30.48	35.04
60	44.29	36.83	41.39
64	46.83	39.37	43.93
68	49.37	41.91	46.47
72	51.91	44.45	49.01
80	56.99	49.53	54.09
100	69.69	62.23	66.79

SPECIFICATIONS

Material

Insulator: PBT, glass reinforced, rated UL 94V-0

Contact: Phosphor Bronze

Electrical

Current Rating: 1 Amp

Contact Resistance: 30 mΩ max.

Insulation Resistance: 1000 MΩ min.

Dielectric Withstanding Voltage: 250V AC for 1 minute

Operating Temperature: -40°C to +105°C

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PPROJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

MOD50-BD-2Xxx-LF
SERIES | LEADFREE
2X05:10 WAY
2X50:100 WAY
DIP 180°
BOX

DESCRIPTION: