



SPECIFICATION NOTES:

1. Electrical:

- 1.1 Voltage rating: 125 VAC RMS
- 1.2 Current rating: 1.5 A
- 1.3 Contact resistance: 50 milliohms max
- 1.4 Insulation resistance: 1000 megaohms min @ 500 VDC
- 1.5 Dielectric strength: 1000 VAC RMS 50Hz, 1MIN.

2. Mechanical:

- 2.1 Retention strength: 50N MIN FOR 60S±5S
- 2.2 Operating life: 750 CYCLES MIN
- 2.3 Insertion force: 30N MAX.

3. Material & finish:

- 3.1 Housing: PC clear
- 3.2 Contact: copper alloy plated with gold
- 3.3 Operating temperature: -40 °C to +80 °C.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm SCALE 1:1

DATE

SIZE A4

X. ± 0.30

.X ± 0.20

.XX ± 0.15

.XXX ± 0.05

ANG ±

P PROJECTION

照片框

ORDER INFORMATION

MP-R-0606DR-LF
SERIES | LEADFREE
6P6C | D TYPE RIGHT
ROUND OUTLET

DESCRIPTION: