



2 PRONGS FOR STRANDED WIRE
多芯線用二叉型金片
(MP-R-0808B)

2 PRONGS FOR SOLID WIRE(SS)
單芯線用大拐角型金片
(MP-R2-0808B)

3 PRONGS FOR SOLID WIRE(S)
單芯線用三叉型金片
(MP-R3-0808B)

Material :

1. 塑膠材質 Housing Material : (Polycarbonate(PC) UL 94V-0 UL 94V-2)
2. 金片型式 Contact Type : (二叉型金片 2 prongs for STRANDED wire 大拐角金片 2 prongs for SOLID wire 三叉金片 3 prongs for SOLID wire)
3. 鍍金厚度 Gold Plating : (F $\mu\ell$ Flash) 3 $\mu\ell \geq 0.0762 \mu\text{m}$ 6 $\mu\ell \geq 0.1524 \mu\text{m}$ 15 $\mu\ell (\geq 0.381 \mu\text{m})$ 30 $\mu\ell (\geq 0.762 \mu\text{m})$ 50 $\mu\ell \geq 1.27 \mu\text{m}$)
4. 金片材質 Contact Material : (青銅 Bronze 磷青銅 Phosphor Bronze)

Remark:

1. 適用24或 26 AWG 線材。 Available for 24 or 26 AWG wire.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司
www.morethanall.com

DRAWING BY CY		X, ± .X ± .XX ± .XXX ± ANG ±
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	
DATE		
SIZE A4	PJECTION	

照片框

ORDER INFORMATION

MP-Rx-0808B-LF
SERIES | LEADFREE
DOUBLE S.R.
8P8C
ROUND OUTLET | BLANK: 2 PRONGS FOR STRANDED WIRE
2: 2 PRONGS FOR SOLID WIRE(SS)
3: 3 PRONGS FOR SOLID WIRE(S)

DESCRIPTION: