



P/N	A ± 0.25
MPCI-W40-124XL	4.0
MPCI-W52-124XL	5.2
MPCI-W56-124XL	5.6
MPCI-W80-124XL	8.0
MPCI-W92-124XL	9.2

NOTES:

1. MATERIAL:

HOUSING: LCP, UL94V-0, Black
CONTACT: PHOSPHOR BRONZE(C5191R-H)

2. FINISH:

CONTACT:
CONTACT AREA: G/F GOLD PLATED
SOLDER AREA: MATTE TIN PLATED
UNDER PLATING: NICKEL PLATED.

3. SPECIFICATION:

CURRENT RATING: 0.3A / (1PIN)
VOLTAGE RATING: 25V AC
DIELECTRIC WITHSTANDING: 250V AC FOR 1 MINUTE
CONTACT RESISTANCE: 30m Ω Max.
INSULATION RESISTANCE: 500M Ω Min
OPERATING TEMPERATURE: -40°C to +90°C
DURABILITY: 50 CYCLES MIN.
INSERTION FORCE: 20N MAX.
WITHDRAWAL FORCE: 2N

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X, \pm
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG $\pm 1^\circ$

P PROJECTION

照片框

ORDER INFORMATION

MPCI-Wxx-124XL-LF

SERIES	LEADFREE	NON LATCH
90°SMT	40:4.0mm HIGH	52:5.2mm HIGH
	56:5.6mm HIGH	80:8.0mm HIGH
	92:9.2mm HIGH	

DESCRIPTION: Mini PCI Socket Pitch:0.8mm Series (w/o Latch)