



MATERIAL

Contacts: Gold plating in localized area over nickel undercoat
 IDC terminals: Phosphor bronze with nickel plating
 Housing: Fire retardent thermal plastic UL94V-0
 Interface dimensions conforms to FCC part 68 subpart F requirements
 Adaptable to cable OD 4 - 8mm
 Conductor acceptance 22 - 24 AWG solid conductor with max, 1.27mm Insulation OD
 Wiring color code- T568A and T568B
 RoHS 2 compliant

WIRE RANGE

Conductor Diameters: 0.41 mm (0.016 in) 26 AWG - 0.51 mm (0.020 in) 24 AWG
 Insulation Diameters: 0.8 mm (0.032 in) - 1.0 mm (0.039 in)
 Cable Diameters: 5 mm (0.197 in) - 7 mm (0.276 in)

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PJECTION

照片框

ORDER INFORMATION

MPKC6A-IKP50-0808-LF

SERIES

||

||

||

||

||

||

LEADFREE

50u" GOLD
 PLASTIC
 BLACK
 IDC

DESCRIPTION: