



Material: *Insulator: PBT UL 94V-0 with 30% GF
 *Contact: Brass, Gold Plating

Dimensional & Ordering Information:

Circuits	Dimensions				Pcs/Bag	Circuits	Dimensions				Pcs/Bag
	A	B	C	D			A	B	C	D	
4	6.65	2.00	5.0	4.85	1000	28	30.65	26.00	29.0	28.85	1000
6	8.65	4.00	7.0	6.85		30	32.65	28.00	31.0	30.85	
8	10.65	6.00	9.0	8.85		32	34.65	30.00	33.0	32.85	
10	12.65	8.00	11.0	10.85		34	36.65	32.00	35.0	34.85	
12	14.65	10.00	13.0	12.85		36	38.65	34.00	37.0	36.85	
14	16.65	12.00	15.0	14.85		38	40.65	36.00	39.0	38.85	
16	18.65	14.00	17.0	16.85		40	42.65	38.00	41.0	40.85	
18	20.65	16.00	19.0	18.85		42	44.65	40.00	43.0	42.85	
20	22.65	18.00	21.0	20.85		44	46.65	42.00	45.0	44.85	
22	24.65	20.00	23.0	22.85		46	48.65	44.00	47.0	46.85	
24	26.65	22.00	25.0	24.85	48	50.65	46.00	49.0	48.85		
26	28.65	24.00	27.0	26.85	50	52.65	48.00	51.0	50.85		

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.25
 .XX ± 0.15
 .XXX ± 0.08
 ANG ±

PJECTION

照片框

ORDER INFORMATION

MPVK-RB-2Xxx-LF

SERIES

LEADFREE
 2X02:04WAY
 2X25:50WAY
 KEY WAY+TWO LOCK
 DIP 90°

DESCRIPTION: