



Material: * Insulator: Nylon 6T UL 94V-0 (Black)
 * Contact: Brass, Gold Flash Plated

Dimensional & Ordering Information:

Circuits	Dimensions				Circuits	Dimensions			
	A	B	C	D		A	B	C	D
4	6.65	2.00	5.0	4.85	28	30.65	26.00	29.0	28.85
6	8.65	4.00	7.0	6.85	30	32.65	28.00	31.0	30.85
8	10.65	6.00	9.0	8.85	32	34.65	30.00	33.0	32.85
10	12.65	8.00	11.0	10.85	34	36.65	32.00	35.0	34.85
12	14.65	10.00	13.0	12.85	36	38.65	34.00	37.0	36.85
14	16.65	12.00	15.0	14.85	38	40.65	36.00	39.0	38.85
16	18.65	14.00	17.0	16.85	40	42.65	38.00	41.0	40.85
18	20.65	16.00	19.0	18.85	42	44.65	40.00	43.0	42.85
20	22.65	18.00	21.0	20.85	44	46.65	42.00	45.0	44.85
22	24.65	20.00	23.0	22.85	46	48.65	44.00	47.0	46.85
24	26.65	22.00	25.0	24.85	48	50.65	46.00	49.0	48.85
26	28.65	24.00	27.0	26.85	50	52.65	48.00	51.0	50.85

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT / mm SCALE 1:1
 DATE

X, ±
 .X ± 0.25
 .XX ± 0.15
 .XXX ± 0.08
 ANG ±

照片框

ORDER INFORMATION

MPVK-RBN6T-2Xxx-LF
 SERIES | LEADFREE
 | 2X02:04WAY
 | 2X25:50WAY
 | NYLON 6T
 | KEY WAY+TWO LOCK
 | DIP 90°

煜倫股份有限公司

www.morethanall.com

SIZE A4 PROJECTION

DESCRIPTION: