



Recommended P.C.B Layout

MATERIAL

Contact Pin : Brass
 Insulator: PBT UL94-V0
 Plated : Gold flash

SPECIFICATION

Current Rate : 6.5AMP PER PIN (22AWG)
 Insulation Resistance : 5000MΩMin. at DC 500V
 Contact Resistance : 20mΩMax. at DC 100mA
 Dielectric Voltage : AC 500V for one minute
 Operation Temperature : -40°C to + 105°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PPROJECTION

X, ±
 .X ± 0.30
 .XX ± 0.20
 .XXX ±
 ANG ± 3°

照片框

ORDER INFORMATION

MS-D1514732-2X14-LF
 SERIES | LEADFREE
 28 WAY
 DIP 3.2mm
 CONTACT 4.7mm
 TOTAL 15.10mm
 DIP180°

DESCRIPTION: PIN HEADER 2.00*2.00mm STRAIGHT TYPE, DUAL ROWS DUAL INSULATORS