



Recommended P.C.B Layout

MATERIAL
 Contact Pin : Brass
 Insulator: PBT UL94-V0

SPECIFICATION
 Current Rate : 3 AMP
 Insulation Resistance : 5000M Ω Min. at DC 500V
 Contact Resistance : 20m Ω Max. at DC 100mA
 Dielectric Voltage : AC 500V for one minute
 Operation Temperature : -40°C to + 105°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, \pm
 .X \pm 0.30
 .XX \pm 0.20
 .XXX \pm
 ANG \pm 3°

PPOJECTION

照片框

ORDER INFORMATION

MS-D1563426-2X14-LF
 SERIES | | | | LEADFREE
 | | | | 28 WAY
 | | | | DIP 2.6mm
 | | | | CONTACT 3.4mm
 | | | | TOTAL 15.60mm
 | | | | DIP180°

DESCRIPTION: PIN HEADER 2.00*2.00mm STRAIGHT TYPE, DUAL ROWS DUAL INSULATORS