



Recommended P.C.B Layout

**MATERIAL**

Contact Pin : Brass

Insulator : PBT UL94-V0

**SPECIFICATION**

Current Rate : 1 AMP

Insulation Resistance : 5000mΩMin. at DC 500V

Contact Resistance : 20mΩMax. at DC 100mA

Dielectric Voltage : AC 500V for one minute

Operation Temperature : -25°C to +85°C

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ±  
ANG ± 3°

PJECTION

照片框

**ORDER INFORMATION**

MSB-D1223628-2X05-LF  
SERIES | | | | LEADFREE  
| | | | 10 WAY  
| | | | DIP 2.8mm  
| | | | DIP 3.6mm  
| | | | LONG 12.20mm  
| | | | DIP 180°

DESCRIPTION: PIN HEADER 2.00\*2.00mm STRAIGHT TYPE, DUAL ROWS DUAL INSULATORS

煜倫股份有限公司

www.morethanall.com