



Recommended P.C.B Layout

MATERIAL

Contact Pin : Brass
 Insulator : PBT UL94-V0

SPECIFICATION

Current Rate : 1 AMP
 Insulation Resistance : 5000mΩMin. at DC 500V
 Contact Resistance : 20mΩMax. at DC 100mA
 Dielectric Voltage : AC 500V for one minute
 Operation Temperature : -25°C to +85°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 煜倫股份有限公司
 www.morethanall.com

| | | |
|-------------------|-------------|---|
| DRAWING BY CY | | X. ± .X ± 0.30 .XX ± 0.20 .XXX ± ANG ± 3° |
| CHECKED BY GENIUS | | |
| UNIT / mm | SCALE 1 : 1 | |
| DATE | | |
| SIZE A4 | PJECTION | |

照片框

ORDER INFORMATION

MSB-D1223628-2X06-LF
 SERIES | | | | LEADFREE
 | | | | 12 WAY
 | | | | DIP 2.8mm
 | | | | DIP 3.6mm
 | | | | LONG 12.20mm
 | | | | DIP 180°

DESCRIPTION: PIN HEADER 2.00*2.00mm STRAIGHT TYPE, DUAL ROWS DUAL INSULATORS