

備註：

- 1.材料：
 - 1.1.HOUSING：LCP GLASS FIBRE, UL94V-0;
 - 1.2.SHELL：SPCC T=0.3,.
 - 1.3.CONTACT：C2680 T=0.25；
- 2.電鍍：
 - 2.1.SHELL：ALL PLATING Ni 100u"min
 - 2.2.CONTACT：接觸部份GOLD FLASH；其餘部份Sn100u"
- 3.OTHERS：
 - 3.1.A~E IS THE CONTACT RELATIVE POSITIVE POSITION IN 5 PCS.
 - 3.2.MARKED IS THE ORDER OF CHEKING.
 - 3.3.MARKE IS THE MAJOR DIMENSION

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.20
.XX ± 0.10
.XXX ±
ANG ±

PPOJECTION



ORDER INFORMATION

MSB-PRRV-5B-LF
SERIES | | | LEADFREE
5 PIN B TYPE
REVERSED
DIP 90°
MALE

DESCRIPTION: