

HO LE LAYO UT (TO PV IEW )

ELECTRICAL CHARACTERISTICS:  
 RATINGS:DC 30V MAX or AC 40V MAX,3A  
 INSULATION RESISTANCE:  
 100MΩ MIN  
 CONTACT RESISTANCE:50mΩ MAX  
 DIELECTRIC STRENGTH:  
 250V AC/1 MINUTE  
 INSERTION FORCE:3.57kgf MAX.  
 WITHDRAWAL FORCE:0.30~1.02kgf  
 PA9T UL 94 V-0

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS


UNIT/ mm SCALE 1:1

DATE

SIZE A4 PPROJECTION

TOLERANCES ARE

X. ±  
 .X ± 0.30  
 .XX ± 0.20  
 .XXX ± 0.10  
 ANG ± 1°



ORDER INFORMATION

MSB-PW-5B-LF  
 SERIES | LEADFREE  
 5 PIN B TYPE  
 90°SMT  
 MALE

DESCRIPTION: MINI USB 5PIN B MALE SMT(腳高3.5,PING高1.35)