



RECOMMENDED PCB LAYOUT

Specifications:

1. Electrical:

- (Rated voltage) 30V DC
- (Rated current) 1.0A/Contact
- (Contact resistance) 50mW MAX
- (Insulation resistance) 100MW Min
- (Withstand Voltage) 300V AC

2. Material

- (Housing) LCP Black
- (Contact) Copper Alloy C5191
- (Shell) Copper Alloy C6280

3. Finish:

- (Contact) Plated Gold in Mating Area;
in On Solder Talls
- (Shell) Tin Plating

4. (Temperature Range) -30 ~+80

RoHS Compliant

TOLERANCES ARE

DRAWING BY	CY	X. ± 0.35
CHECKED BY	GENIUS	.X ± 0.25
UNIT / mm	SCALE 1 : 1	.XX ± 0.15
DATE		.XXX ± 0.10
		ANG ±

SIZE A4 PPROJECTION

照片框

ORDER INFORMATION

MSB-SR36M1-5B-LF
 SERIES | | | | LEADFREE
 | | | | 5 PIN B TYPE
 | | | | METAL FOOT
 | | | | 3.55mm
 | | | | DIP 90°
 | | | | FEMALE

DESCRIPTION:

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com