



P.C.B. LAYOUT  
SCALE 2.00

Note:

1.Material:

- 1.1 Insulator: PBT UL 94-V0 rated
- 1.2 Contact: phosphor bronze, t=0.25mm
- 1.3 Shell: brass, t=0.4mm

2.specification:

- 2.1 Current rating: 1A MAX
- 2.2 Dielectric withstanding voltage: 500 v(ac) far minuta
- 2.3 Contact resistance: 30 mΩ max
- 2.4 Insulation resistance: 1000 mΩ min at DC 500V.
- 2.5 Temperature range: -55°C~+105°C

3.Finishes:

- 3.1 Contacts: Gold flashed 1U", 3U", 5U", 10U", 15U", 30U"
- 3.2 Shell: Nickel plated.

3	MINI USB 5P銅殼	1	Brass	T=0.4±0.02mm	Nickel Plated	D3520XX
2	MINI USB 5PIN 90° 每端 (每) (2 PIN)	5	PHOSPHOS BRONZE	T=0.25±0.02mm	Gold Plated Over Tin	A0760XX
	MINI USB 5PIN 90° 每端 (每) (3 PIN)					A0760XX-A
1	膠心	1	P.B.T+30%GF		Black/Blue/White	
No.	Part Name	Q'ty	Material	Thickness	Finish	Notes

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

MSB-SRS30-5B-LF  
SERIES | LEADFREE  
5 PIN B TYPE  
SEMI GOLD 30u"  
DIP 90°  
FEMALE

DESCRIPTION: