



NOTES:

- 1.ELECTRICAL SPECIFICATION:  
 CURRNT RATING: 0.8A VOLTAGE RATING: 300 VAC/60S DIELECTRIC WITHSTANDING VOLTAGE: 300VAC INSULATION RESISTANCE: 100MΩ CONTACT RESISTANCE: MAX 120mΩ
- 2.ENVIRONMENTAL  
 OPERATING TEMPERATURE: -15°C TO +85°C STORAGE TEMPERATURE: -30°C TO +85°C

MSB-SS-5B-LF  
 LEADFREE  
 RoHS Compliant

NO.	PART NO:	NAME	MATERIAL	COLOR	QTY
1		Mini USB 5P(F)SMT 180° HOUSING			1PCS
2		Mini USB(2.0)AB TYPE 5P(F)Solder端子			5PCS
3		Mini USB 5P(F Moding)SHIELD	SEE NOTE. 3	SEE NOTE. 3	1PCS
4		Mini USB 5P(F Moding)外套			1PCS
5		Mini USB 5P(F Moding)Back Blug			1PCS



PART NO. MSB-SS-5B

DWG NO. MSB-SS-5B

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE  
 .X±0.2  
 .XX±0.1  
 .XXX±  
 AWG

DESCRIP TION:	Mini USB-5P (F Moding)			
	AREA	REVISIONS	HK	DATE

煜倫股份有限公司