



Recommended PCB Layout(T=0.8)

Specification

*Electrical Characteristics:

Contact Current Rating: 0.5 Amperes.

Dielectric Withstanding Voltage: AC100V r.m.s.

Insulation Resistance: 100 MΩ Minimum.

Contact Resistance: 50 mΩ Maximum.

*Environmental:

Operating Temperature: -25°C~+65°C.

*Environmental:

Mating Cycles: 10,000 Insertions.

*Material:

Insulator: HI-Temp Plastic UL 94V-0 Rated.

Contact: Copper Alloy(t=0.15mm).

Shell: Copper Alloy(t=0.25mm).

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.38
.XX ± 0.25
.XXX ± 0.13
ANG ± 2°

PPOJECTION

照片框

ORDER INFORMATION

MSB-SWEEP-10AB-LF
SERIES POST 10 PIN AB TYPE
LEADFREE
90°SMT
FEMALE

DESCRIPTION: