



NOTE:

1.ELECTRICAL PROPERTIES:

- 1-1.CONTACT CURRENT RATING:1A AT 250V AC MIN.
- 1-2.CONTACT RESISTANCE:50m Ohm MAX
- 1-3.INSULATION RESISTANCE:100M Ohm MIN.
- 1-4.DIELECTRIC WITHSTANDING VOLTAGE:AC 100V/1 MINUTE.

2.MATERIAL:

- 2-1.TERMINAL:PHOSPHOR BRONZE(C5191R-H),T=0.20±0.015mm.
- 2-2.HOUSING:LCP
- 2-3.SHELL : PHOSPHOR BRONZE(C5191R-H),T=0.30±0.01.

3.PLATING:

- 3-1.TERMINAL: GOLD 10u" MIN ON CONTACT AREA,
GOLD FLISH MIN ON SOLDER TAILS,
UNDERPLATED NICKEL OVER ALL 50u" MIN.
- 3-2.SHELL: NICKEL 60u", SMT GOLD FLISH ON ALL AREA

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1

.XX ± 0.25

DATE

.XXX ± 0.15

ANG ±

SIZE A4

P PROJECTION

照片框

ORDER INFORMATION

MSB-SWEEPC-10AB-LF
SERIES | LEADFREE
10 PIN AB TYPE
FEMALE | MYLAR
90°SMT | POST
EAR+EAR

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com