



3	SHELL	1	Brass	T=0.40±0.01mm	Nickel plated
2	CONTAC	5	Phosphor Bronze	T=0.25±0.01mm	Gold flashed
1	HOUSING	1	PBT/LCP		Black
No.	Part Name	Q'ty	Material	Thickness	Finish

Note:
Material:

- 1.1 Insulator: LCP/PBT UL 94-V0 rated
- 1.2 Contact: Phosphor bronze, t=0.25mm
- 1.3 Shell: Brass, t=0.4mm

Specification:

- 1.1 Current rating: 1A MAX
- 2.2 Dielectric withstanding voltage: 500 v(ac) far minuta
- 2.3 Contact resistance: 30 mΩ max
- 2.4 Insulation resistance: 1000 mΩ min at DC 500V.
- 2.5 Temperature range: -55°C~+105°C.

3. Finishes:

- 3.1 Contacts: Gold flashed 1U", 3U", 5U", 10U", 15U", 30U"
- 3.2 Shell: Nickel plated.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

MSB-SWF-5B-LF
SERIES | LEADFREE
5 PIN B TYPE
OFFSET
90°SMT
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: MINI-U.S.B 5P B FEMALE SMT (沉板式)無導柱(端長2.00)