



Recommend P.C.B LAYOUT

備註 /NOTE:

1. 安規
  - 1-1. 規格 /RATING: 5V / 1A
  - 1-2. 絕緣阻抗 /Insulation Resistance: 100M ohm Min at DC 500V
  - 1-3. 絕緣耐壓 /DielectricWithstandingVoltage: AC100V for 1 Minute
  - 1-4. 接觸阻抗 /Contact Resistance: 30m ohm or less
2. 材質 /MATERIAL:
  - 2-1. 膠芯 /Housing:LCP
  - 2-2. 針 /Pin:磷銅 /PHOSPHOR BRONZE
  - 2-3. 銅殼 /Shell:黃銅 /BRASS
3. 電鍍 /electroplate
  - 3-1. 針 /Pin:半金10u"鍍 /GOLD10u"鍍
  - 3-2. 銅殼 /Shell:鍍鎳 /TIN/Nickel

No.	Part Name	Q'ty	Material	Thickness	Finish	Notes
3	SHELL	1	Brass	T=0.40±0.02mm	Nickel Plated	
2	CONTACT	5	Phosphor Bronze	T=0.25±0.02mm	10u"金	
1	HOUSING	1	LCP		Black	

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

MSB-SWFMMC-5AB-LF  
SERIES | | | | LEADFREE  
| | | | 5 PIN AB TYPE  
FEMALE | | | | MYLAR  
| | | | METAL FOOT  
| | | | OFFSET  
| | | | 90°SMT

DESCRIPTION: Mini Usb 5P(F) 破板式 1.45高