



PC BOARD LAYOUT

Material:
 Insulator: PBT UL 94V-0 rated,
 Contact: Phosphor bronze t=0.25mm
 Shell: Phosphor bronze t=0.40mm

Specification:
 Current rating: 1A MAX
 Dielectric withstanding voltage: 500VAC far minuta
 Contact resistance: 30mΩ max
 Insulation resistance: 100MΩ min at DC 500V
 Total mating force: 3.57Kgf max
 Total unmating force: 0.71Kgf min
 Temperature range :-40. C ~+85. C

Finishes:
 Contacts: Gold flashed
 Shell: Nickel plated

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
 .X ± 0.25
 .XX ± 0.15
 .XXX ± 0.075
 ANG ±

PPOJECTION

照片框

ORDER INFORMATION

MSB-SWX-5B-LF
 SERIES | LEADFREE
 | 5 PIN B TYPE
 | NON POST
 | 90°SMT
 FEMALE

DESCRIPTION: MINI-U.S.B 5P A/B FEMALE SMT(无脚)