



FEATURE:

INSULATOR

Glass-Filled P.B.T. is 94V-0 rated

CONTACT

Phosphor Bronze selective gold plating over nickel

SPECIFICATION:

Current Rating : 3 amperes

Contact Resistance : 20 miniohms max.

Operation Temperature : -55°C to +105°C

Voltage Rating : 800 VAC 1 minute

Insulation Resistance : 5000 megaohms min.

Insertion Force : 412 grams max. per pair

Withdrawal Force : 32 grams min. per pair

CONTACTS NO.	DIM A	DIM B	DIM C	DIM D	DIM E
15/31	68.18	61.47	54.52	51.81	44.45
18/36	77.61	71.99	64.04	60.33	53.97
21/41	83.95	77.34	71.39	66.68	60.32
22/44	91.31	83.69	76.74	73.03	66.67
28/56	119.35	112.74	95.79	92.08	85.72
30/61	115.71	109.19	102.14	98.43	92.07
36/72	134.75	128.14	121.19	117.48	111.12
40/81	147.45	141.84	133.89	130.18	123.82
43/86	156.97	151.36	143.41	139.71	133.35
51/100	179.21	172.59	165.64	161.93	155.57

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

MSL-DME19-xxx-LF
SERIES | LEADFREE
030~100WAY
DIP 19.0mm
MIDDLE EARS
DIP 180°

DESCRIPTION: EDGE Connector 3.175mm Mounting Ears

煜倫股份有限公司

www.morethanall.com