



MATERIAL & FINISH

- * Contact: Brass
Plating: G=Gold Plated
T=Tin Plated
- * Insulator: Thermoplastic polyester
- * Resist to Soldering Heat: Max. 260°C, 5 Sec.
- * Solderability: 235°C, 5 Sec.
- * Current Rating: 3A
- * Voltage rated: 100VRMS / 150VDC
- * Contact Resistance : 10 Milliohm
- * Insulator Resistance : 10000M ohm min.
- * Dielectric Strength : 1000 VRMS Min
- * Rated Voltage : 100 VRMS / 150VDC
- * Temperature: - 55°C TO + 125°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1 : 1

.XX±

DATE

.XXX±

ANG±

煜倫股份有限公司

www.morethanall.com

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

MSP-Dx-2Xxx-LF
SERIES | LEADFREE
2X02:04 WAY
2X40:80 WAY
DIP 180°
BLANK: TIN
G:GOLD

DESCRIPTION: 2.0mm Pin Header Double Row Str