



Technical Data

Material:

Pin(outer sleeve): Brass,machined CuZn38Pb2

Plating(outer sleeve):

Tin plated:2 μ m/80 μ "Ni, 5 μ m/200 μ "Sn

Gold Plated:2 μ m/80 μ "Ni,Full gold

Insulator(black): Black (PPS) UL94V-0

Electrical:

Current rating: 3Amps/contact max.

Contact resistance: $\leq 4\text{m}\Omega$ /contact

Insulation resistance: $\geq 5000\text{M}\Omega$ at V=500V

Dielectric Withstanding Voltage: 1000V AC Min

Operaing voltage: 60VAC/DC

Mechanical:

Operaing temperatures: Gold Plsted:-55 $^{\circ}$ C to+125 $^{\circ}$ C

Tin plated:-40 $^{\circ}$ C to+105 $^{\circ}$ C

Soldering temperature: +260 $^{\circ}$ C,10s max.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, \pm

.X \pm

.XX \pm

.XXX \pm

ANG \pm

照片框

ORDER INFORMATION

MSP-Rx-1Xxx-LF
SERIES | LEADFREE
1X02:02 WAY
1X40:40 WAY
G:GOLD PLATE
T: TIN PLATE
DIP 90 $^{\circ}$

DESCRIPTION: 2.00mmPitch SIP Adapters SMT DIP Spacing 2.00mm Pin Length 10.30mm

煜倫股份有限公司

www.morethanall.com