



MATERIAL:

- RJ:
- HOUSING & COVER—PBT POLYESTER UL94V-0 MIXED GLASS FIBER. STANDARD COLOR—GRAY OR BLACK.
  - CONTACTS—0.35mm THICK PHOS-BRONZE PLATED WITH 30u" HARD GOLD AND GOLD FLASH IN SOLDER AREA.
  - SHIELD—0.20mm THICK COPPER ALLOY, PLATED WITH 20u" MIN. NICKEL.
- USB:
- HOUSING—PBT POLYESTER UL94V-0 MIXED GLASS FIBER. STANDARD COLOR—GRAY.
  - CONTACTS—0.25mm THICK PHOS-BRONZE PLATED WITH GOLD FLASH AND 100u" TIN PLATED IN SOLDER AREA.
  - SHIELD—0.30mm THICK SPCC, 80u" MIN. NICKEL PLATED.
- CAVITY CONFIRMS TO FCC RULES AND REGULATIONS PART 68,SUBPART F.

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.25  
.XX ± 0.20  
.XXX ± 0.10  
ANG ±

PJECTION

照片框

ORDER INFORMATION

MUJ-KX30-88A1-LF  
SERIES | | | LEADFREE  
| | | USB A TYPE  
| | | 8P8C  
| | | 30u" GOLD  
| | | FULL SPRING  
| | | BLACK

DESCRIPTION: MODULAR JACK, RJ45 STACKED OVER USB CONN, WITHOUT LED, DIP TYPE

煜倫股份有限公司

www.morethanall.com