



RECOMMENDED PCB LAYOUT
TOP VIEW
TOLERANCE:±0.05mm
PCB THICKNESS: 1.60±0.05mm

Electrical Characteristics :
Insulation Resistance : 500MΩ Min.
Contact Resistance : 50mΩ Max.
Withstand Voltage : 1000 VAC 1 minute.
Current Rating : 1.5A

Material:
Housing: Thermoplastic , UL94V-0
Contact : Selective Gold Plating
Terminal: 0.35mm(RJ) &0.25mm(USB)Thickness Copper Alloy
Plated With Gold And Tin In Solder Area.
Front Shell: Alloy ,Nickel Plating
Back Shell : Alloy



MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X, ±
.X ± 0.25
.XX ± 0.15
.XXX ± 0.075
ANG ±

PJECTION

照片框

ORDER INFORMATION

MUJL-KX06GY-88A1-LF

SERIES | | | | LEADFREE
| | | | A TYPE
| | | | 8P8C
DIP 90° | LEFT LED / RIGHT LED
NON EAR | GREEN / YELLOW
06u" GOLD

DESCRIPTION: RJ45 & USB , Shielded , Receptacle Horizontal , 2x1 Ports , Tht , With LED