



Electronics Test :

1. Contact Resistance : 2 Ω Max.
2. 100% open & short test (set at 20 KΩ)
3. At DC = 300V , Insulation Resistance : 20 MΩ Min.
4. Test Condition : Temperature : 25 ± 5°C , Humidity : 50% RH Max.

| | | | | |
|----|---|--------|---|----|
| P1 | 6 | GREEN | 6 | P2 |
| | 5 | YELLOW | 5 | |
| | 4 | ORANGE | 4 | |
| | 3 | RED | 3 | |
| | 2 | BROWN | 2 | |
| | 1 | BLACK | 1 | |

WIRING TABLE

| | | |
|------|---|--------|
| 3 | SOCKET CONTACT | 12 PCS |
| 2 | HOUSING, 6-POS., 2.50mm PITCH, WHITE | 2 PCS |
| 1 | FLAT RIBBON WIRE, 22 AWG x 6C, UL 1007 (併線) | A/R |
| ITEM | DESCRIPTION | Q'TY |

MWX2-060622C1-F25C-LF
LEADFREE

RoHS Compliant

| | | | | | |
|----------|-----------------------------|-----------|--|------------------------------------|-------------------------------|
| | PART NO. MWX2-060622C1-F25C | | TOLERANCES ARE X. ± .X ± .XX ± .XXX ± ANG | DESCRIPTION: WIRE HARNESS ASSEMBLY | |
| | DWG NO. MWX2-060622C1-F25C | | | | |
| 焯倫股份有限公司 | FILE NO. | | DRAWING BY | | AREA REVISIONS DATE |
| | UNIT / mm | SCALE 1:1 | PROJECTION | | |