

P1	6	GREEN	6	P2
	5	YELLOW	5	
	4	ORANGE	4	
	3	RED	3	
	2	BROWN	2	
	1	BLACK	1	

WIRING TABLE

Electronics Test :

1. Contact Resistance : 2 Ω Max.
2. 100% open & short test (set at 20 KΩ)
3. At DC = 300V , Insulation Resistance : 20 MΩ Min.
4. Test Condition : Temperature : 25 ± 5°C , Humidity : 50% RH Max.

3	SOCKET CONTACT	12 PCS
2	HOUSING, 6-POS., 2.50mm PITCH, WHITE	2 PCS
1	FLAT RIBBON WIRE, 22 AWG x 6C, UL 1007 (併線)	A/R
ITEM	DESCRIPTION	Q'TY

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION



ORDER INFORMATION

MWX2-060622C1-FxxC-LF
SERIES | LEADFREE
18C:180mm
06 TO 06 WAY | FEMALE TO FEMALE
COMBO WIRE
22 AWG

DESCRIPTION: WIRE HARNESS ASSEMBLY