








NOTES:

- 1.HUOSING: LCP HIGH-TEMP THERMOPLASTIC UL94V-0 COLOR:BLACK
- 2.TERMINAL:PHOSPHOR BRONZE
PLATING:GOLD FLASH IN CONTACT AREA/100μ"MIN.MATTE TIN
PLATE IN SOLDER AREA.OVERALL 50μ" MIN. NICKEL.



3D VIEW



MATING HEIGHT

MATING HEIGHT	H1	H2
5.0	4.5	4.0
8.0	7.5	4.0
10	4.5	9.0
13	7.5	9.0
15	9.5	9.0
18	12.5	9.0
20	14.5	9.0
23	17.5	9.0
25	19.5	9.0

NO.of contacts	Dimensions			
	A.	B.	C.	D.
10	11.3	3.2	8.2	8.8
20	15.3	7.2	12.2	12.8
30	19.3	11.2	16.2	16.8
40	23.3	15.2	20.2	20.8
50	27.3	19.2	24.2	24.8
60	31.3	23.2	28.2	28.8
70	35.3	27.2	32.2	32.8
80	39.3	31.2	36.2	36.8
100	47.3	39.2	44.2	44.8
120	55.3	47.2	52.2	52.8
140	63.3	55.2	60.2	60.8
160	71.3	63.2	68.2	68.8
180	79.3	71.2	76.2	76.8
200	87.3	79.2	84.2	84.8

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ± 0° 30'

照片框

ORDER INFORMATION

NP0843-PxxxEP1-xxx-LF

SERIES

MALE

EAR

045:UNMATED HIGH 4.50mm

195:UNMATED HIGH 19.50mm

LEADFREE
010~200WAY

POST

DESCRIPTION:0.8mm BTB PLUG