







A: 8.00 mm B: 2.50 mm C: 3.00 mm

MATERIAL

HOUSING : NY6T, UL-94V0
COLOR : BLACK
CONTACT : BRASS
PLATED : GOLD-FLASH

SPECIFICATION

CURRENT : 1A
OPERATING TEMPERAURE : -55° C TO +105° C
CONTACT RESISTANCE : 20 MILLIOHMS MAX
INSULATION RESISTANCE: 1000 MEGAOHMS MIN
WITHSTAND VOLTAGE : 500 V AC/Minute

CONTACTS

	2×12	2×25	2×38
	2×13	2×26	2×39
	2×14	2×27	2×40
2×02	2×15	2×28	2×41
2×03	2×16	2×29	2×42
2×04	2×17	2×30	2×43
2×05	2×18	2×31	2×44
2×06	2×19	2×32	2×45
2×07	2×20	2×33	2×46
2×08	2×21	2×34	2×47
2×09	2×22	2×35	2×48
2×10	2×23	2×36	2×49
2×11	2×24	2×37	2×50

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.38
.XX ± 0.25
.XXX ±
ANG ± 5°

照片框

ORDER INFORMATION

P-D252530-2Xxx-LF
SERIES DIP180° LEADFREE
2X02:04WAY
2X50:100WAY
DIP 3.0mm
CONTACT 2.5mm
BASE 2.5mm

DESCRIPTION: PIN HEADER 1.27*2.54 180° H:2.50 2*XXPIN