



RECOMMENDED P.C.B LAYOUT



MATERIAL
HOUSING : THERMOPLASTIC UL94V-0
CONTACT : COPPER ALLOYS

SPECIFICATION
CURRENT: 1A
OPERATING TEMPERATURE: -55°C TO +105°C
CONTACT RESISTANCE : 20 MILLIOHMS MAX
INSULATION RESISTANCE : 5000 MEGAOHMS MIN
DIELECTRIC STRENGTH : 1000 VAC MIN
DURABILITY : 100 CYCLES
RETENTION FORCE : 700g MIN

FINISH : GOLD FLASH PLATED

CONTACTS	
1X2	1X26
1X3	1X27
1X4	1X28
1X5	1X29
1X6	1X30
1X7	1X31
1X8	1X32
1X9	1X33
1X10	1X34
1X11	1X35
1X12	1X36
1X13	1X37
1X14	1X38
1X15	1X39
1X16	1X40
1X17	1X41
1X18	1X42
1X19	1X43
1X20	1X44
1X21	1X45
1X22	1X46
1X23	1X47
1X24	1X48
1X25	1X49
	1X50

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. ±
.X ± 0.38
.XX ± 0.25
.XXX ±
ANG ± 5°

P PROJECTION

照片框

ORDER INFORMATION

PA-D15xxyy-1Xxx-LF
SERIES
DIP 180°
CONTACT
40:4.0mm
...
BASE 1.5mm
LEADFREE
1X02:02WAY
DIP 1X50:50WAY
23:2.3mm
...

DESCRIPTION: PIN HEADER 1.27*1.27mm STRAIGHT TYPE, SINGLE ROW