


P. C. B . LAYOUT



A: 5.50 mm
 B: 3.00 mm
 C: 1.70 mm

MATERIAL

HOUSING : NY6T, UL94V-0
 CAP : NY6T, UL94V-0
 CONTACT : COPPER ALLOYS
 PLATED : GOLD FLASH
 COLOR : BLACK

SPECIFICATION

CURRENT : 1A
 OPERATING TEMPERATURE: -55° C TO +105° C
 CONTACT RESISTANCE : 20 MILLIOHMS MAX
 INSULATION RESISTANCE: 1000 MEGAOHMS MIN
 WITHSTANDING VOLTAGE : 500 V AC/minute

CONTACTS			
	2 × 12	2 × 25	2 × 38
	2 × 13	2 × 26	2 × 39
	2 × 14	2 × 27	2 × 40
2 × 02	2 × 15	2 × 28	2 × 41
2 × 03	2 × 16	2 × 29	2 × 42
2 × 04	2 × 17	2 × 30	2 × 43
2 × 05	2 × 18	2 × 31	2 × 44
2 × 06	2 × 19	2 × 32	2 × 45
2 × 07	2 × 20	2 × 33	2 × 46
2 × 08	2 × 21	2 × 34	2 × 47
2 × 09	2 × 22	2 × 35	2 × 48
2 × 10	2 × 23	2 × 36	2 × 49
2 × 11	2 × 24	2 × 37	2 × 50


RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 焯倫股份有限公司
 www.morethanall.com

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT / mm SCALE 1 : 1
 DATE
 SIZE A4 PPROJECTION

X. ±
 .X ± 0.38
 .XX ± 0.25
 .XXX ±
 ANG ± 5°



ORDER INFORMATION

PA-V17XC-2Xxx-LF
 SERIES LEADFREE
 2X02:04 WAY
 2X50:100 WAY
 180°SMT CAP
 NON POST
 HIGH 1.7mm

DESCRIPTION: