







RECOMMENDED P.C.B LAYOUT



A: 5.50 mm B: 3.00 mm C: 2.60 mm

MATERIAL

HOUSING :NY6T, UL-94V0
CAP :NY6T, UL-94V0
CONTACT :COPPER ALLOYS
PLATED :GOLD-FLASH
COLOR :BLACK

SPECIFICATION

CURRENT : 1A
OPERATING TEMPERAURE : -55° C TO +105° C
CONTACT RESISTANCE : 20 MILLIOHMS MAX
INSULATION RESISTANCE: 1000 MEGAOHMS MIN
WITHSTAND VOLTAGE : 300 V AC MIN

CONTACTS	2X26
2X2	2X27
2X3	2X28
2X4	2X29
2X5	2X30
2X6	2X31
2X7	2X32
2X8	2X33
2X9	2X34
2X10	2X35
2X11	2X36
2X12	2X37
2X13	2X38
2X14	2X39
2X15	2X40
2X16	2X41
2X17	2X42
2X18	2X43
2X19	2X44
2X20	2X45
2X21	2X46
2X22	2X47
2X23	2X48
2X24	2X49
2X25	2X50

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X, ±
.X ± 0.38
.XX ± 0.25
.XXX ±
ANG ± 5°

PPOJECTION

照片框

ORDER INFORMATION

PA-V26X30C-2Xxx-LF
SERIES 180°SMT HIGH 2.6mm
LEADFREE 2X02:04 WAY 2X50:100 WAY
CAP CONTACT 3.0mm NON POST

DESCRIPTION: PIN HEADER 1.27 SMT+CAP H:2.0