


PAL JACK FOR RG59 CABLE

FERRULE	BRASS	NICKEL
CONTACT PIN	BRASS	GOLD
INSULATOR	TEFLON	WHITE
BODY	BRASS	NICKEL
DESCRIPTION	MATERIAL	FINISH



PAL PLUG FOR RG59 CABLE

FERRULE	BRASS	NICKEL
CONTACT PIN	BRASS	NICKEL
INSULATOR	DELRIN	WHITE
BODY	BRASS	NICKEL
DESCRIPTION	MATERIAL	FINISH

RG-59/U COAXIAL CABLE

1.Conductor	Material	Copper Clad Steel
	Stranded	0.643
2.Insulation	Material	PE
	Thickness	1.56mm ±0.05mm
	OD:	3.7mm ±0.1mm
3.Braid	Material	FOIL
	Material	Bare Copper Wire
	Strinded	16/7/0.12mm
	PITCH	29mm ± mm
4.Jacket	Coverage	80%
	Material	PVC
5.Dielection Strength	OD:	6.0mm ±0.1mm
		AC 2300V/1Min
6.Impedance		73 ohm ±3 ohm

照片框

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

ORDER INFORMATION

PALX2-1S1S59-E1M5-LF

SERIES

ST/ST

RG 59

1500mm

LEADFREE

MALE TO FEMALE

DESCRIPTION: PAL JACK TO PAL PLUG FOR RG59 CABLE L=1,500mm