


PCI Express Connectors Pinout

Shorting

Side A	Pin #	Side B
Signal	1	Power
Power	2	Power
Power	3	Power
Ground	4	Ground
Signal	5	Signal
Signal	6	Signal
Signal	7	Ground
Signal	8	Power
Power	9	Signal
Power	10	Power
Signal	11	Signal
Ground	12	Signal
Signal	13	Ground
Signal	14	Signal
Ground	15	Signal
Signal	16	Ground
Signal	17	Signal
Ground	18	Ground
Signal	19	Signal
Ground	20	Signal
Signal	21	Ground
Signal	22	Ground
Ground	23	Signal
Ground	24	Signal
Signal	25	Ground
Signal	26	Ground
Ground	27	Signal
Ground	28	Signal
Signal	29	Ground
Signal	30	Signal
Ground	31	Signal
Signal	32	Ground
Signal	33	Signal
Ground	34	Signal
Signal	35	Ground
Signal	36	Ground
Ground	37	Signal
Ground	38	Signal
Signal	39	Ground
Signal	40	Ground
Ground	41	Signal

Side A	Pin #	Side B
Ground	42	Signal
Signal	43	Ground
Signal	44	Ground
Ground	45	Signal
Ground	46	Signal
Signal	47	Ground
Signal	48	Signal
Ground	49	Ground
Signal	50	Signal
Ground	51	Signal
Signal	52	Ground
Signal	53	Ground
Ground	54	Signal
Ground	55	Signal
Signal	56	Ground
Signal	57	Ground
Ground	58	Signal
Ground	59	Signal
Signal	60	Ground
Signal	61	Ground
Ground	62	Signal
Ground	63	Signal
Signal	64	Ground
Signal	65	Ground
Ground	66	Signal
Ground	67	Signal
Signal	68	Ground
Signal	69	Ground
Ground	70	Signal
Ground	71	Signal
Signal	72	Ground
Signal	73	Ground
Ground	74	Signal
Ground	75	Signal
Signal	76	Ground
Signal	77	Ground
Ground	78	Signal
Ground	79	Signal
Signal	80	Ground
Signal	81	Signal
Ground	82	Signal

Shorting



NOTES (Ground Pin Position):

- (36P): A12, A15, A18,
B13, B16, B18,
- (64P): A12, A15, A18, A20, A23, A24, A27, A28, A31,
B13, B16, B18, B21, B22, B25, B26, B29, B32,
- 98P: A12, A15, A18, A20, A23, A24, A27, A28, A31, A34, A37, A38, A41, A42, A45, A46, A49,
B13, B16, B18, B21, B22, B25, B26, B29, B32, B35, B36, B39, B40, B43, B44, B47, B49,
- 164P: A12, A15, A18, A20, A23, A24, A27, A28, A31, A34, A37, A38, A41, A42, A45, A46, A49,
A51, A54, A55, A58, A59, A62, A63, A66, A67, A70, A71, A74, A75, A78, A79, A82,
B13, B16, B18, B21, B22, B25, B26, B29, B32, B35, B36, B39, B40, B43, B44, B47, B49,
B52, B53, B56, B57, B60, B61, B64, B65, B68, B69, B72, B73, B76, B77, B80.

#POS RFE	DIM'A'	DIM'B'	DIM'C'	DIM'D'	DIM'E'	DIM'F'	DIM'G'
(36P)	25.00	27.00	7.65	6.00	9.15	8.15	28.00
(64P)	39.00	41.00	21.65	20.00	23.15	22.15	42.00
98P	56.00	58.00	38.65	37.00	40.15	39.15	59.00
164P	89.00	91.00	71.65	70.00	73.15	72.15	92.00

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.35
.XX ± 0.25
.XXX ± 0.15
ANG ± 3°

照片框

ORDER INFORMATION

PCIX5-VPEC -xxx-LF

SERIES
CAP
EAR
POST
180°SMT

LEADFREE
036~164WAY

DESCRIPTION: PCI Express 5.0 SMT Type(A)(8.20) (SMT Metal Posts)