

Specifications:

Current rating:2.0Amps

Voltage rating:20V AC,DC

Operating Temperature:-40°C ~ +85°C

Contact resistance:50mohm Max

Insulation resistance:10,000Mohm min.

Mechanical Characteristic:

Total Working Travel:1.5mm

Spring Force:100 \pm 20g At Normal Working Level

Mechanical Life:2000 Cycle Min

Material And Finish

Spring:stainless steel


SPring Plating:Gold flash over 40u" Silver Plated

Mater-sleeve::Brass

Mater-sleeve Plating:Gold flash over 120u" Nickel Plated

Pin:Brass

Pin Plating:Gold flash over 120u" Nickel Plated



照片框

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. \pm

.X \pm

.XX \pm

.XXX \pm

ANG \pm

ORDER INFORMATION

PGP-D-095944-LF

SERIES

LEADFREE

MAX WORKING HEIGHT 4.40mm

TOTAL LONG 5.90mm

0.90 ϕ

180°

DESCRIPTION: POGO PINFINISHED PRODUCTS (THREE PARTS)