




RECOMMENDE PCB LAYOUT

Note:

.Materials

Plunger & Barrel : Brass

Spring : Stainless Steel

.Plating

Plunger : 10 μ " min. Au over, 50 μ " min. Ni

Barrel : 10 μ " min. Au over, 50 μ " min. Ni

.Electrical

Contact Resistance : 50m Ω max

at Working Height(Quiescence)

Current Rating: DC 12V , 1A

.Mechanical

Total Height : 8.00 mm

Working Height : 7.00 mm

Spring Force : 80g $\pm$ 20% at Working Height

Durability : 10,000 Cycles minimum

照片框

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, $\pm$
.X $\pm$ 0.20
.XX $\pm$ 0.10
.XXX $\pm$ 0.05
ANG $\pm$

ORDER INFORMATION

PGP-D-099585-LF
SERIES
LEADFREE
MAX WORKING HEIGHT 8.5mm
TOTAL LONG 9.5mm
0.9 ϕ
DIP 180°

DESCRIPTION: