



NOTES(备注):

1. 材质:
 针轴: Brass C3604 (黄铜C3604)
 内管: Brass C3604 (黄铜C3604)
 弹簧: SUS304 不锈钢
2. 电镀:
 针轴: 镀镍50~120 micro-inch 后镀金3 micro-inch
 针管 镀镍50~120 micro-inch 后镀金3 micro-inch
3. 电气特性
 电压&电流: 直流电12伏 ;3安
 接触阻抗: 在工作高度时最大阻抗50毫欧(静态)
4. 机械特性
 在正常工作高度的弹力20G±8G 寿命: 10,000次(最少)
5. 产品符合ROHS要求.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X, ±
 .X ± 0.30
 .XX ± 0.25
 .XXX ± 0.15
 ANG ± 2°

PJECTION

照片框

ORDER INFORMATION

PGP-D40-098679-LF

SERIES

LEADFREE

MAX WORKING HEIGHT 7.90mm

TOTAL LONG 8.60mm

0.90 Ø

DIP 180° 4.0mm

DESCRIPTION: POGO-PIN