

NOTE

1.Material

Plunger: Brass 3604
Barrel: Brass 3604
Spring: SUS304

2.Plating

Plunger: 16 micro-inch minimum Au over 50 micro-inch nickel
Barrel: 4 micro-inch minimum Au over 50 micro-inch nickel

3.Electrical

Rated current & voltage: DC 12V; 1.0A Max.
Contact resistance: 100 mohm maximum at normal working height(quiessence)

4.Mechanical


Spring force: 70g±20g at normal working height
Durability: 10,000 cycles(minimum)

5.To ensure the best usage,please operate it based on the working height

Based on the engineering drawings,shall not exceed the maximum allowed compression

6.To avoid arcing issue, The adaptor start to power supply after connector mated fully.

7.RoHS compliant product.



RoHS Compliant

TOLERANCES ARE

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ± 0.15

UNIT / mm

SCALE 1 : 1

.XX ± 0.10

DATE

.XXX ±

ANG ± 2°

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

PGP-VC-062417-LF

SERIES

LEADFREE

1.78mm WORKING HIGH

2.40mm TOTAL HIGH

0.6mm DIA

COVER

180°SMT

DESCRIPTION:

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com