



Notes:

1. Material (材质):

- 1) Body: Brass
- 2) Plunge: Brass
- 3) Spring: Stainless steel wire

2. Plating (电镀):

- 1) Body: Gold plating over Nickel plating
(Body: 镍底镀金3u^m)
- 2) Plunger: Gold plating over Nickel plating
(Plunger: 镍底镀金3U^m)

3. Mechanical (机械性能)

- 1) Durability (寿命): 20000 cycle min

4. Electrical (电性能)

- 1) Contact resistance (接触阻抗): 30mohm MAX
- 2) Voltage rating (额定电压): 36V DC Max
- 3) Current rating (额定电流): 1A

5. Working stroke (工作行程): 1.0

6. Spring (弹力): 60g±20g (with full travel length)

7. Housing / 塑胶: PA46

8. Magnetic / 磁铁: N52

9. 4*3500GS

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.50

.X ± 0.20

.XX ± 0.10

.XXX ± 0.05

ANG ± 1°

PPOJECTION

照片框

ORDER INFORMATION

PGP40-SMS-02-LF

SERIES

LEADFREE

02 WAY

MAGNETIC SUCTION

SOLDER

DESCRIPTION: