



Note:

... **Materials:**

Pin: Lead-free C6801, plating xxU" Min Au over 60~100U" Ni ;
 Housing: Black HTN+30%GF UL94 V-0;

... **Electrical:**

Voltage: 12 V.
 Current: 5.0 A Max.
 Contact resistance: 50mΩ Max (PIN).
 100% open and short test.

... ROHS or REACH compliant product.

... Salt spray test: 48 H.

... & Key inspection dimension .

10pin	54.00	46.00	42.00	38.00	01u-99u	01u-99u
9pin	50.00	42.00	38.00	34.00	01u-99u	01u-99u
8pin	46.00	38.00	34.00	30.00	01u-99u	01u-99u
7pin	42.00	34.00	30.00	24.00	01u-99u	01u-99u
6pin	38.00	30.00	24.00	20.00	01u-99u	01u-99u
5pin	34.00	26.00	20.00	16.00	01u-99u	01u-99u
4pin	30.00	22.00	16.00	12.00	01u-99u	01u-99u
3pin	26.00	18.00	12.00	8.00	01u-99u	01u-99u
2pin	22.00	14.00	8.00	4.00	01u-99u	01u-99u
NO.	A±0.20	B±0.10	C±0.20	D±0.10	Barrel (Film thickness)	Plunger (Film thickness)

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X, ±
 .X ± 0.20
 .XX ± 0.10
 .XXX ±
 ANG ±

照片框

ORDER INFORMATION

PGS40-SPE-1Xxx-LF

SERIES

EAR

PANEL

SOLDER

LEADFREE
 1X02:02 WAY
 1X10:10 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: