



Electronics Test :

1. Contact Resistance : $2\ \Omega$ Max.
2. 100% open & short test (set at $20\ K\Omega$)
3. At DC = 300V , Insulation Resistance : $20\ M\Omega$ Min.
4. Test Condition : Temperature : $25 \pm 5^\circ\text{C}$, Humidity : 50% RH Max.

9	SPIRAL WRAPPING BAND, O.D. = 8.0mm, L = 80mm, TRANSPARENT	1 PC
8	HEAT SHRINKABLE TUBE, $\varnothing 8.0\text{mm}$, L = 20.0mm, BLACK	2 PCS
7	HEAT SHRINKABLE TUBE, $\varnothing 8.0\text{mm}$, L = 35.0mm, BLACK	2 PCS
6	PVC TUBE, , $\varnothing 6.68\text{mm}$, L = 830mm, BLACK	1 PC
5	PVC TUBE, , $\varnothing 6.68\text{mm}$, L = 170mm, BLACK	1 PC
4	SOCKET CONTACT	20 PCS
3	HOUSING, 14-POS., 2.54mm PITCH, W/CPK, BLACK	1 PC
2	HOUSING, 16-POS., 2.54mm PITCH, W/CPK, BLACK	1 PC
1	WIRE, 28 AWG, UL 1007	A/R
ITEM	DESCRIPTION	Q'TY

P1	1	PURPLE	14	P2
	5	BROWN	2	
	6	WHITE	1	
	7	YELLOW	4	
	8	GREEN	3	
	9	PINK	6	
	10	GRAY	5	
	11	RED	8	
	12	BLUE	7	
	15	BLACK	13	

WIRING TABLE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. $\pm$

.X $\pm$

.XX $\pm$

.XXX $\pm$

ANG $\pm$

PPOJECTION

照片框

ORDER INFORMATION

PVKCX2-B07B0828-F1M15-LF

SERIES

LEADFREE

1150mm

FEMALE TO FEMALE

28 AWG

14 TO 16 WAY

DESCRIPTION: