

- * Material : Nylon UL 94V-0 or 94V-2
- * Integrally molded polarization
- * Positive lock
- * Integrally molded mounting ears is available on plug housing only
- * 1,2,3,4,5,6,9,12,15 circuits available

PWL-S-xXxx-LF
LEADFREE

RoHS Compliant

mm (inch)

Circuits	Max-Rated		Dimensional Information	
	Amps	Voltage	Plug	Receptacle
1	12A	600V		

PWL-S-1X01

PWL-S-1X02

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. **PWL-S-1Xxx**

DWG NO. **PWL-S-1Xxx**

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIP TION:

AREA

REVISIONS

HK

DATE

煜倫股份有限公司

Circuits	Max-Rated		Dimensional Information	
	Amps	Voltage	Plug	Receptacle

MORETHANALL CONNECTORS ASSEMBLIES		PART NO. PWL-S-xXxx									
煜倫股份有限公司		DWG NO. PWL-S-xXxx		CHECKED BY CY	TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIP TION:					
		FILE NO.		DRAWING BY							
		UNIT / mm	SCALE 1 : 1	PROJECTION 		AREA	REVISIONS	HK	DATE		