


SPECIFICATION:

Contact Rating :10A125/250VAC TV-8 (A.) TV-10 (C)
 10A/142A 250VAC ~LT85 (A) (D) (S) (N) (F)
Contact Resistance :50 milliohm max.
Insulation Resistance :500 megohms min. 500VDC.
Withstand Voltage :2,000 VAC-1 minute
Endurance :10,000 Cycles
Stroke :Lock stroke 2.6±0.5mm
 full stroke 4.2±0.5mm
Operating Force :500±200gf
 RoHS Compline

APPROVAL FILE NO:

UL FILE NO: E105856
 CSA FILE NO: 112904
 VDE FILE NO: 40014604
 NEMKO FILE NO: P05203711
 SEMKO FILE NO: 502270
 DEMKO FILE NO: 313272-01
 FI FILE NO: 21532



主要尺寸(*)	重要尺寸
A1	A 31.2
B1	B 25.5
C1	C 18.5
D1	D 18.8
E1	E 12.5
F1	F 20.3
G1	G 9.0
H1	H
I1	I
J1	J

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PPOJECTION

照片框

ORDER INFORMATION

PWSW49-QPE-04-LF

SERIES | | LEADFREE
 | | 04 WAY
 | | PANEL EAR
 SQUARE

DESCRIPTION: