



NOTE :

1. TERMINAL PLATING : TIN(Sn)
2. FLAMMABILITY RATING : UL94V-2
3. INSULATION SIZE : 4.06mm MAX D.A.
4. WIRE RANGE : 16-14A.W.G
5. MAXIMUM ELECTRICAL RATING : 105° C 600 VOLTS MAX.
6. TERMINAL MATERIAL : BRASS(H)
7. INSULATION MATERIAL : NYLON
8. INSULATION COLOR : BLUE
9. THICKNESS : 0.4

公差 TOLERANCE 項目 ITEM	NEMA TAB	W ±0.20	L ±1.0	D ±0.30	C ±0.20	WIRE STRIP LENGTH
尺寸 SIZE	.032*.250 (0.8*6.35)	9.30	21	4.40	2.10	6.50

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

Q250-FT8NFD-14-LF
SERIES | | | | | T LEADFREE
| | | | | 14-16 AWG
| | | | | D TYPE
FEMALE | FULL
TERMINAL | NYLON
THICKNESS 0.8mm

DESCRIPTION: