





INSERT RING COLORS



PCB LAYOUT
(BOTTOM VIEW)

NO.	NAME	MATERIAL	FINISH	Q'TY
1	BARREL	BRASS 0.40	NICKEL PLATED	2
2	INSERT RING	PBT G.F.	RED.WHITE	4
3	COVER	ABS	BLACK	2
4	HOUSING	ABS	WHITE	1
5	TERMINAL	BRASS 0.50	TIN PLATED	2
6	TERMINAL	BRASS 0.50	TIN PLATED	2

Specification:

Contact Resistance: 30m Ohm. Max. At AC 100mA Max.1KHz
Insulation Resistance: 100M Ohm Min. At 500V DC.
Rated Voltage And Current: DC 12V,2A Max ; AC 100V,1A Max.
Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute
Durability (Life Test): 4000 Cycles
Insertion Force: 0.3~3.0 Kg.
Extraction Force: 0.3~3.0Kg.

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. ± 0.38

.X ± 0.25

.XX ± 0.13

.XXX ± 0.05

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

RCAB2-JD24RRWW-03-LF

SERIES

LEADFREE

03 WAY

RED.RED/WHITE.WHITE

HIGH 24.5mm

DIP 180°

JACK

DESCRIPTION: RCA JACK