


RECOMMENDED P.C.B. LAYOUT (T=1.60)
TOLERANCE: ±0.05 (BOTTOM VIEW)

SCHMATIC



WASHER COLOR	A	GREEN
	B	BLUE
	C	RED

6	TERMINAL	1	C2680 t=0.4	Cu/Sn PLATED
5	TERMINAL	1	C2680 t=0.4	Cu/Sn PLATED
4	TERMINAL	1	C2680 t=0.4	Cu/Sn PLATED
3	OUTER CONTACT	1	C2680 t=0.4	Cu/Sn PLATED
2	WASHER	3	PBT 4815	UL-94V0
1	HOUSING	1	PBT 4815	UL-94V0(BLACK)
LTR	PART NAME	QTY	MATERIAL	REMARK

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

RCAC1-JR48E1GBR-04-LF

SERIES | | | | LEADFREE
04WAY
JACK | | | | COLOR A.B.C
DIP90° | | | | GREEN/BLUE/RED
EAR
4.8mm

DESCRIPTION: PIN JACK