



XX	OPTO GATE COLOR	WASHER COLOR	PLATED
01	LIME(577C)	ORANGE(157C)	MATTED TIN
02	LIME(577C)	BLACK	MATTED TIN
03	LIME(577C)	YELLOW	MATTED TIN
04	BLACK	YELLOW	MATTED TIN

14	WASHERS	1	PBT	UL-94V0(ORANGE157C)
13	INSULATOR	1	PBT	UL-94V0
12	SEALED PLATE	1	BRASS	Cu NI PLATED
11	OPTO SPRING	1	SUS	
10	OPTO GATE	1	PA66	UL-94V0(LIME 577C)
9	OPTO FRAME	1	PA66	UL-94V0(BLACK)
8	OPTO-TERMINAL	3	PHOSPHOR BRONZE	TIN/NI PLATED
7	OPTO-HOSING	1	LCP	UL-94V0(BLACK)
6	3# SPRING	1	PHOSPHOR BRONZE	Cu MATTED TIN PLATED
5	2# TERMINAL	1	BRASS	Cu MATTED TIN PLATED
4	1# TERMINAL	1	BRASS	Cu MATTED TIN PLATED
3	OUTER CONTACT	1	BRASS	Cu NI PLATED
2	COVER	1	PA9T	UL-94V0(BLACK)
1	HOUSING	1	PBT	UL-94V0(BLACK)
NO.	DESCRIPTION	QUANTITY	MATERIAL	REMARK

T:1.6 Dimensions of PC board holes
Tolerance : ±0.05(Printed-top view)

RCAPOF-FRP1SE-03T-LF
LEADFREE
RoHS Compliant

	PART NO. RCAPOF-FRP1SE-03T		TOLERANCES ARE .X ± .XX ± .XXX ± AWG	DESCRIP TION:				
	DWG NO. RCAPOF-FRP1SE-03T							CHECKED BY CY
焯倫股份有限公司	FILE NO.		DRAWING BY		AREA	REVISIONS	HK	DATE
	UNIT / mm	SCALE 1:1	PROJECTION					