



RECOMMEND P.C.B LAYOUT
TOP VIEW

MATERIALS

1. HOUSING : P.B.T (UL 94V-0).
2. TERMINAL : BRASS, GOLD PLATING ON CONTACT, TIN PLATING ON SOLDER TAIL.
3. RCA JACK BUSHING : BRASS.
4. DRIVE IC : COPPER ALLOY, TIN PLATING.

SPECIFICATION

RCA JACK :

1. CURRENT RATING : 0.3 AMP. MAX.
2. DIELECTRIC WITHSTANDING VOLTAGE : 500V AC R.M.S. FOR ONE MINUTE.
3. INSULATION RESISTANCE : 100M OHMS MIN. AT 500V DC
4. CONTACT RESISTANCE : 50m OHMS MAX.
5. OPERATING TEMPERATURE : -25°C TO +70°C.
6. MATING FORCE :
RCA : 0.3 ~ 3.0kgs
DRIVE IC : 0.4 ~ 3.5kgs.
7. UNMATING FORCE : 0.3 ~ 3.0kgs.
RCA : 0.3 ~ 3.0kgs
DRIVE IC : 0.4 ~ 3.5kgs.

RCAPOF-TSE-03-LF
LEADFREE

RoHS Compliant

	PART NO. RCAPOF-TSE-03		TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIP TION: FIBER OPTICS COMBO CONNECTOR Ø8.30mm DIA. RCA JACK & FIBER OPTICS TRANSMITTER
	DWG NO. RCAPOF-TSE-03			
	FILE NO.		DRAWING BY	AREA
	UNIT / mm	SCALE 1:1	PROJECTION	
				HK
				DATE